

## DIAMOND SHINE® ULTRA HIGH-SPEED FLOOR COATING

A metal cross-linked, all-purpose, high speed coating, **DIAMOND SHINE** produces a tough, long lasting base and a diamond-like brilliant wet-look shine in a less frequent ultra high speed burnishing program.

### FEATURES

- Ideal for less frequent maintenance program
- Hard, durable coating
- High initial gloss
- Produces a deep wet-look shine
- Saves time and labor
- Self-sealing
- Classified by UL as to slip resistance only



### RECOMMENDED FLOOR SURFACES

All resilient tile floors and most types of terrazzo, marble, concrete, and quarry tile

### PRODUCT DATA

Description:	Acrylic co-polymer emulsion
Appearance:	Milky white
Fragrance:	Slight ammoniacal
Coverage:	2500-3000 sq ft per gal 61-74 sq m per liter
Non-Volatile Solids:	18.0 ± 0.5%, ASTM D2834-95 (2001)
Specular Gloss (60.):	>85, ASTM D1455-87 (1997)
Buffability:	Excellent
Detergent Resistance:	Excellent ASTM D3207-92 (1996) e1
Removability:	Excellent
Viscosity (Brookfield):	<10 centipoise @ 68.F. (20.C)
Slip Resistance:	Meets ASTM D2047-99 requirements. Classified by UL as to slip resistance only.
Drying time:	Approximately 30 minutes
Shelf Life:	1 year, ASTM D1791-93 (1998)
Density:	8.6 lb per gal @ 68.F. 1.03 kg per liter @ 20.C
Freeze/Thaw:	Passes 3 cycles, ASTM D3209-93 (1998)

### PRECAUTIONS

Keep out of the reach of children. Keep container sealed when not in use. Avoid freezing. If frozen, allow to return to room temperature slowly and then mix thoroughly before using.

### ORDERING INFORMATION

Product #104FS:	2 x 2.5 gallon per case (2 x 9.5 liters)
Product #104MP:	4 x 1.06 gallon per case (4 x 4 liters)

### DIRECTIONS FOR USE: INITIAL APPLICATION

1. Remove old coating and sealer with the recommended Pioneer Eclipse stripper following label directions. For optimum results, use a Pioneer Eclipse autoscrubber or stripping machine with recommended Pioneer Eclipse pads or brushes.
2. Use a clean mop or autoscrubber to rinse the floor twice using a Pioneer Eclipse neutral cleaner. Rinse floor again with clean, cold water and allow to dry.
3. **OPTIONAL:** Apply 2 thin coats of Pioneer Eclipse sealer to protect high-traffic areas and old or porous floors.
4. Apply 4-6 coats of Diamond Shine Floor coating with a clean, synthetic mop.
 

**Note:** Do not exceed an initial application of a combined 6 coats of coating and sealer.
5. Allow floor to dry thoroughly between coats and prior to burnishing.
 

**Note:** To prevent contamination do not pour unused product from bucket into original container.

### DIRECTIONS FOR USE: ROUTINE MAINTENANCE

1. Sweep floor daily with either a mop treated with EnviroStar Green® Dust Mop Treatment, or with an untreated dust mop.
2. Mop or autoscrub as necessary with a Pioneer Eclipse Neutral Cleaner following label directions.
3. Restore as needed with a Pioneer Eclipse maintainer.
4. Burnish as desired with recommended Pioneer Eclipse machine and pad.
5. As needed, perform a deep scrub and recoat applying an additional 1-2 coats of Diamond Shine Floor Coating.
6. Allow floor to dry thoroughly between coats and prior to burnishing.
7. When stripping is necessary, remove coating and sealer with a recommended Pioneer Eclipse stripper.

Pioneer Eclipse®

